

3MP Outdoor Fixed-focal 4G Pan & Tilt Network Camera

DH-P3AE-PV-4G



Series Overview

The Active Defense Series Small PT Camera delivers advanced performance and functionality. Upon detecting an intrusion, it promptly activates sound and light alarms, while simultaneously transmitting critical information to your mobile device for instant alerts. The camera also features two-way talk, enabling real-time communication with individuals on the site. Additionally, its Smart Dual Illuminator enhances visibility, allowing the camera to capture clear, full-color videos and images whether day or night, thereby providing reliable evidence of events while minimizing light pollution. Thanks to its 4G network capability, the camera also delivers continuous surveillance, even in areas with limited Wi-Fi access, making it an ideal choice for remote outdoor locations such as farms, ranches and orchards.



3MP

Clear images with sharp details



4G Connection

Expands your connectivity with 4G



One Camera for 360° View

360° monitoring without blind spots



Al Human Detection

Focuses on what matters and reduces false alarms



AI Vehicle Detection

Focuses on what matters and reduces false alarms



Smart Dual Light

Captures color details for post-event review



Sound and Light Alarm

Provides instant alarms to deter intruders



Two-way Talk

Communication anytime, anywhere



Auto Tracking

Automatic tracking of targets



IP66 Protection

Withstands harsh environments



H.265

Advanced H.265 compression technology



Supports Micro SD Card

Low-cost storage



Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.











Specifications

Camera

Image Sensor 1/2.8" CMOS Max Resolution 2304 (H) × 1296 (V)

30 m (98.43 ft) (warm light); 30 m (98.43 ft) (IR) Illumination Distance

Electronic Shutter Speed 1/25 s-1/100.000 s Illuminator Number 2 (IR light); 2 (warm light)

Lens

Focal Length 4.0 mm Max. Aperture

Field of View H: 73.85°; V: 43.43°; D: 86.56°

Iris Control Fixed

PTZ

Pan: 0° to 345° Pan/Tilt Range Tilt: 0° to +90°

Smart Event

IVS Tripwire and intrusion

Human Detection Human detection; Auto-tracking

Vehicle Detection

Intelligence

SMD SMD 3.0

Video

Smart H.265+;H.265;Smart H.264+;H.264B;H.264M; H.264H;MJPEG(Sub Stream 1) Video Compression

Main stream: 3M/720p/640 × 360@ (1–25/30 fps) Sub stream 1: D1/VGA/CIF@(1–25/30 fps) Video Frame Rate

H264: 64-8,192 kbps H265: 25-6,400 kbps Video Bit Rate

Auto (ICR); Color/B/W Day/Night

DWDR

Motion Detection Yes Image Rotation 180°

Audio

Audio Compression PCM; G.711a; G.711Mu; G.726

Built-in MIC Yes Built-in Speaker Yes

Network

EU LTE-FDD: B1/B3/B5/B7/B8/B20/B28 Wireless Carrier Frequency Band LA LTE-FDD: B2/B3/B4/B5/B7/B8/B28/B66

Max. Transmission Power 4G: Power class3:23 dBm ± 2 dB

Storage Micro SD card (support max. 256 GB);

DMSS Management Software

Mobile Client iOS: Android

General

Certifications CE

Power Supply 12 VDC, 1 A ± 10%

Basic: 3W Max: 9 W (illuminator + PTZ) Power Consumption

Power Adapter Included

Operating Temperature -30 °C to +55 °C (-22 °F to +131 °F)

Operating Humidity

TVS 2000 V lightning proof; surge protection; voltage Protection transient protection; Waterproof and Dustproof

Camera Button Reset button Casing Material

140.5 mm × Φ111.0 mm (5.53" × Φ4.37") Product Dimensions

Net Weight 0.5 kg (1.10 lb)

What's in the box



Installation Position Map × 1







Waterproof Connector



Documents: QR Code × 1



Power Adapter × 1

Power:







Legal and regulation information × 1 Certification \times 1

Quick Start Guide × 1



Wireless Frequency Band Paper \times 1 (-EUR model only)



Warranty Card × 1 (-EUR



model only)

